



CALL US AT:
800-572-1975
TOLL FREE

HBP-ENCOREIII



For use with Printer Models: Zebra EncoreIII
Replacement for OEM Battery No: DC15002-2C

CELL / SPECIFICATION OPTIONS AVAILABLE:

No.	Chemistry	Capacity(mAh)	V	Cell Brand	Cell Model	Weight (g/oz.)		CHG. TEMP.	DCH. TEMP.
1	Nimh	2300	7.2	Yuasa	AA	10	0.35	0°C to 40°C	-20°C to 60°C

Charge:	Trickle / Standard / Rapid			
Housing Material:	PANLITE™ L-1250Y Polycarbonate (PC)			
Sealing Method:	Ultrasonic Welding			
External Contacts Material:	Gold Plated Nickel			
Internal Cell Pack Welding:	Pure Nickel Tabs, Spot Welded			
LWH dimensions (mm):	114.0	X	83.03	X 32.7
LWH dimensions (inch):	4.49	X	3.27	X 1.29

SAFETY FEATURES:

This battery pack incorporates safety devices designed to prevent damage, overheating, fire or explosion in case of such as accidental short-circuit or use of a wrong or faulty charger. Individual electrical cells comprise a reasonable safety vent to prevent the buildup of a resealable safety vent to prevent the buildup of internal pressure. Li-ion battery packs contain additional circuitry designed to prevent overcharging and over-discharging, which can harm the internal cells and lead to premature battery end-of-life, and swelling in extreme cases.

This product was developed and is continually tested in conjunction with original device and charging equipment. It is guaranteed for complete compatibility with these. Specifications of all components used meets or exceeds that of original equipment.