



**CALL US AT:**  
**800-572-1975**  
**TOLL FREE**

## HBM-1727LFP



**For use with Barcode Scanner Models:** Symbol PDT81XX, PPT27XX, PPT28XX, PPT88XX, SPT17XX, SPT18XX

**Replacement for OEM Battery No:** 21-60332-01 / KT-661579-01 / FATPACK

### CELL / SPECIFICATION OPTIONS AVAILABLE

Chemistry	Capacity(mAh)	V	Cell Brand	Cell Model	Weight (g/oz.)		CHG. TEMP.	DCH. TEMP.
Li-Ion	3800	3.7	Sanyo	UF103450JPV	88.3	3.1	0°C to 40°C	-20°C to 60°C

**Charge:** Trickle / Standard / Rapid  
**Housing Material:** PANLITE L-1250Y Polycarbonate (PC)  
**Sealing Method:** Ultrasonic Welding  
**External Contacts Material:** Gold Plated Nickel  
**Internal Cell Pack Welding:** Pure Nickel Tabs, Spot Welded  
**LWH dimensions (mm):** 57.1 X 37.0 X 23.2  
**LWH dimensions (inch):** 2.25 X 1.46 X 0.91

#### SAFETY FEATURES:

This battery pack incorporates safety devices to prevent damage, overheating, fire or explosion in case of non-typical events such as accidental short-circuit or use of a wrong or faulty charger. Individual electrical cells comprise a resealable safety vent to prevent the buildup of internal pressure. Li-ion battery packs contain additional circuitry designed to prevent overcharging and over-discharging, which can harm the internal cells and lead to premature battery end-of-life, and swelling in extreme cases.

This product was developed and continually tested in conjunction with original device and charging equipment. It is guaranteed for complete compatibility with these. Specifications of all components used meets or exceeds that of original equipment.