



CALL US AT: 800-572-1975 TOLL FREE

HBM-CK31L



For use with Barcode Scanner Models: Intermec CK30 / 31 Replacement for OEM Battery No: 318-020-001

CELL / SPECIFICATION OPTIONS AVAILABLE:

I	No.	Chemistry	Capacity(mAh)	V	Cell Brand	Cell Model	We	eight (g/oz.)	CHG. TEMP.	DCH. TEMP.
I	1	Li Ion	2600	7.4	Sanyo	UR18650FK	140.1	4.94	0°C to 40°C	-20°C to 60°C

Charge:	Trickle / Standard / Rapid					
Housing Material:	PANLITE™ L-1250Y Polycarbonate (PC)					
Sealing Method:	Ultrasonic Welding					
External Contacts Material:	Gold Plated Nickel					
Internal Cell Pack Welding:	Pure Nickel Tabs, Spot Welded					
LWH dimensions (mm):	85.0 X 65.1 X 24.	85				
LWH dimensions (inch):	3.35 X 2.56 X 0.9	8				

SAFETY FEATURES:

This battery pack incorporates safety devices designed to prevent damage, overheating, fire or explosion in case of such as accidental short-circuit or use of a wrong or faulty charger. Individual electrical cells comprise a reasonable safety vent to prevent the buildup of a resealable safety vent to prevent the buildup of internal pressure. Li-ion battery packs contain additional circuitry designed to prevent overcharging and over-discharging, which can harm the internal cells and lead to premature battery end-of-life, and swelling in extreme cases.

This product was developed and is continually tested in conjunction with original device and charging equipment. It is guaranteed for complete compatibility with these. Specifications of all components used meets or exceeds that of original equipment.